

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

## FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF  
  
A PORTION OF THE NORTH BOUNDARY,  
  
A PORTION OF THE SUBDIVISIONAL LINES,  
  
THE SUBDIVISION OF SECTIONS 1, 2, 11, AND 12,  
  
AND  
  
THE SURVEY OF THE SUBDIVISION OF SECTION 1,  
  
IN  
  
TOWNSHIP 2 NORTH, RANGE 22 EAST  
  
OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Jerry L. Thomas and Richard L. Houston*  
*Cadastral Surveyors*

Under special instructions dated and approved *July 3, 1996*, which provided for the surveys included under Group Number 845, and assignment instructions dated *July 10, 1996*, and Supplemental Assignment Instructions dated *August 30, 1996*.

Survey commenced *August 13, 1996*  
Survey completed *June 10, 1997*

# INDEX DIAGRAM

Township 2 South, Range 22 East

6	5	4	3	2 6 7	3 1 5
7	8	9	10	11 4	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 1 .....Page 8  
 Subdivision of Section 2 .....Page 10  
 Subdivision of Section 11 .....Page 12  
 Subdivision of Section 12.....Page 16

## TOWNSHIP 2 NORTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections 1, 2, 11, and 12, and the survey of the subdivision of section 1, of T. 2 N., R. 22 E., Salt Lake Meridian, Utah.

**History of Surveys****Surveyed by****Retr. or Resurveyed by****NORTH BOUNDARY**

All	S.P. and J.R. Stewart	1906		
Portion			G.D. Voorhees	1958

**SOUTH BOUNDARY**

All	J.C. Clark	1938		
-----	------------	------	--	--

**EAST BOUNDARY ( Ashley Guide Meridian )**

All	S.P. and A.J. Stewart	1906		
Portion			J.C. Clark	1938
Portion			G.D. Voorhees	1958

**WEST BOUNDARY**

Portion	S.P. and J.R. Stewart	1906		
Portion	J.C. Clark	1938		

**SUBDIVISION**

Portion	S.P. and A.J. Stewart	1906		
Portion	J.C. Clark	1938		
Portion			G.D. Voorhees	1959

**MEANDERS**

Portion	S.P. and J.R. Stewart	1906		
Portion	J.C. Clark	1938		

**HOMESTEAD ENTRY SURVEYS**

Portion	J.C. Brown	1913		
Portion	J.C. Clark	1938	J.C. Clark	1938

**DUTCH JOHN TOWNSITE**

All	G.D. Voorhees	1959		
-----	---------------	------	--	--

## TOWNSHIP 2 NORTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

## REMONUMENTATION

Portion                      A. Nelson                      1961

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 845, dated July 3, 1996.

The directions of lines were determined by hour angle observations of the Sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The townsite of Dutch John, Utah, included in this survey comprises portions of sections 1, 2, 11, and 12. The survey provides for the subdivision of the townsite into blocks and lots of size and dimension as determined by existing improvements, such as fences, streets and buildings. The lots are of unequal area, and every effort was made during this survey to protect existing improvements.

There are other small surveys included in this survey. The details of these surveys along with the survey of the townsite are represented upon the plats only.

Four control stations were established, and will function as B.L.M. Control Stations around the perimeter of the Dutch John Townsite. The geographic position of these control stations were determined by a tie to HARN station "SWSA 9 RESET", by the Global Positioning System.

The geographic position of B.L.M. Control Station No. 1, is as follows:

Latitude 40° 55' 32.2154" N.                      Longitude 109° 23' 33.1428" W.  
N.A.D. 1983. Elev. 6,428.0 ft.

The geographic position of B.L.M. Control Station No. 2, is as follows:

Latitude 40° 55' 53.7982" N.                      Longitude 109° 23' 31.3333" W.  
N.A.D. 1983. Elev. 6,323.7 ft.

The geographic position of B.L.M. Control Station No. 3, is as follows:

Latitude 40° 56' 18.7506" N.                      Longitude 109° 24' 34.2659" W.  
N.A.D. 1983. Elev. 6,356.5 ft.

The geographic position of Harn Station "SWSA 9 RESET" as published by the National Geodetic Surveys, is as follows:

Latitude 41° 00' 25.96055" N.                      Longitude 109° 39' 45.84771" W.  
N.A.D. 1983. Elev. 6,095.8 ft.

## TOWNSHIP 2 NORTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

The geographic position of the E-W 1/64 section corner of sections 2 and 11, which is also a B.L.M. Control Station, is as follows:

Latitude 40° 55' 56.7438" N.  
N.A.D. 1983

Longitude 109° 24' 26.0930" W.

The mean magnetic declination as determined from numerous readings throughout the survey is: 13° East.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 2 N., R. 22 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
S.P. and J.R. Stewart in 1906,  
and the Resurvey by G.D. Voorhees in 1958

---

Beginning at the 1/4 section corner of sections 1 and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1958 resurvey of a portion of the north boundary of T. 2 N., R. 22 E.

N. 89° 47.9' W., between sections 1 and 36, north boundary.

Over mountainous land.

**20.051** Point for the W 1/16 section corner of sections 1 and 36, north boundary.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

W 1/16	<u>S36</u>
	S1
	1997

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, north of the corner.

**40.102** The corner of sections 1, 2, 35, and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1958 resurvey of a portion of the north boundary of T. 2 N., R. 22 E.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2 N., R. 22 E., Salt Lake Meridian, Utah

From the S-N 1/64 section corner of sections 11 and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

From this corner, point selected for B.L.M. control Station No. 1, bears S. 56° 56.2' E., 13.977 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

BLM  
  
 CONTROL PT 1  
 1996

Control point No. 1, is located on the west side of airport road.

N. 0° 03.5' W., between sections 11 and 12.

Over nearly level land.

10.002

The N 1/16 section corner of sections 11 and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E., from which

An iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, a reference monument, bears N. 89° 14.5' E., 107.2 ft. dist., with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

An iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, a reference monument, bears S. 1° 05.5' E., 253.8 ft. dist., with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

An iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, a reference monument, bears S. 89° 15.0' W., 171.7 ft. dist., with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

An iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, a reference monument, bears N. 0° 01.5' W., 107 ft. dist., with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

N. 0° 03.5' W., beginning new measurement.

**2.600** Approximate center line of South Boulevard.

**3.850** Approximate center line of 5th Avenue.

**10.500** Approximate center line of South Center Street; thence over public school ground.

**19.655** E. edge of paved portion of 6th Avenue.

**19.825** The corner of sections 1, 2, 11, and 12, monumented with a railroad spike, set flush with surface of road, as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E., from which

An iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, a reference monument, bears S. 89° 57.0' E., 63.7 ft. dist., with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

An iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, a reference monument, bears S. 0° 04.5' E., 97.3 ft. dist., with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

From the 1/4 section corner of sections 1 and 12, monumented an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

S. 89° 56.6' W., between sections 1 and 12.

Over nearly level land.

**20.093** The W 1/16 section corner of sections 1 and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

From this corner, point selected for B.L.M. Control Station No. 2, bears S. 54° 51.0' W., 7.604 chains distance.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

BLM  
  
 CONTROL PT 2  
 1996

Control point No. 2, is located on the north side of Dutch John townsite.

---

S. 89° 54.3' W., beginning new measurement.

**20.065** The corner of sections 1, 2, 11, and 12.

---

N. 0° 02.3' W., between sections 1 and 2.

Over nearly level land.

**9.928** The S-S 1/64 section corner of sections 1 and 2, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

---

N. 0° 01.5' W., beginning new measurement.

**10.031** The S 1/16 section corner of sections 1 and 2, monumented with an iron post, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

---

N. 0° 02.7' W., beginning new measurement.

**20.003** The 1/4 section corner of sections 1 and 2, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above collar of stone, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E.

---

N. 0° 03.3' W., beginning new measurement.

**19.945** Point for the N 1/16 section corner of sections 1 and 2.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N 1/16  
S2 | S1  
1997

Corner is located 38 links E. of trail road.

**39.890** The corner of sections 1, 2, 35, and 36, north boundary, hereinbefore described.

From the corner of sections 1, 2, 11, and 12.

N. 89° 45.7' W., between sections 2 and 11.

Over rolling land.

**19.902** The E 1/16 section corner of sections 2 and 11, monumented with an iron post, 30 inches long, 2 1/2 inches diameter, buried 12 inches below the surface of the ground, with brass cap marked as described in the official record of 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E., from which

An iron post, 2 1/2 inches diameter, set as a reference marker, bears  
N. 43° 16' W., 78.7 ft. dist., firmly set, projecting 6 inches above ground,  
with brass cap marked as described in the official record of the 1959 resurvey  
of a portion of the subdivisional lines of T. 2 N., R. 22 E.

An iron post, 2 1/2 inches diameter, set as a reference marker, bears N. 62° 24' E.,  
38.7 ft. dist., firmly set, projecting 6 inches above ground, with brass cap  
marked as described in the official record of the 1959 resurvey of a portion  
of the subdivisional lines of T. 2 N., R. 22 E.

N. 89° 45.3' W., beginning new measurement.

**19.957** The 1/4 section corner of sections 2 and 11, monumented with an iron post, 30 inches long, 2 1/2 inches diameter, buried 12 inches below surface of road, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E., from which

An iron post, 2 1/2 inches diameter, set as a reference marker, bears  
N. 20° 41.0' W., 47.6 ft. dist., firmly set, projecting 6 inches above ground,  
with brass cap marked as described in the official record of the 1959 resurvey  
of a portion of the subdivisional lines of T. 2 N., R. 22 E.

An iron post, 2 1/2 inches diameter, set as a reference marker, bears S. 21° 55' W.,  
111.9 ft. dist., firmly set, projecting 6 inches above ground, with brass cap  
marked as described in the official record of the 1959 resurvey of a portion  
of the subdivisional lines of T. 2 N., R. 22 E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 58.5' W., beginning new measurement.

- 9.996** The E-W 1/64 section corner of sections 2 and 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey of a portion of the subdivisional lines of T. 2 N., R. 22 E. This corner will also function as a B.L.M. Control Station.

---

Dependent Resurvey of a Portion of the Subdivision  
of Section 1, T. 2 N., R. 22 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
G.W. Voorhees in 1959

---

From the center 1/4 section corner of section 1, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 1 of T. 2 N., R. 22 E.

N. 0° 12.4' W., on the N - S center line of section 1.

Over rolling land.

- 19.824** Point for the center N 1/16 section corner of section 1.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad | \quad \text{S } 1 \\ \text{C} \\ 1997 \end{array}$$

- 39.648** The 1/4 section corner of sections 1 and 36, north boundary, hereinbefore described.
- 

From the center 1/4 section corner of section 1.

S. 89° 51.8' W., on the E - W center line of section 1.

Over rolling land.

- 20.105** The center W 1/16 section corner of section 1, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the 1959 survey of the subdivision of section 1 of T. 2 N., R. 22 E.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION  
OF SECTION 1, T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 89° 50.9' W., beginning new measurement.

**20.103**

The 1/4 section corner of sections 1 and 2.

---

From the W 1/16 section corner of sections 1 and 12.

N. 0° 02.8' E., on the N - S center line of the SW 1/4 of section 1.

Over gentle rolling land.

**9.983**

The center S-SW 1/16 section corner of section 1, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 1 of T. 2 N., R. 22 E.

---

S. 89° 45.0' W., on the E - W center line of the SW 1/4, of the SW 1/4 of section 1.

Over gentle rolling land.

**20.080**

The S-S 1/64 section corner of sections 1 and 2.

---

Survey of a Portion of the Subdivision  
of Section 1, T. 2 N., R. 22 E., Salt Lake Meridian, Utah

---

From the center W 1/16 section corner of section 1.

N. 0° 07.8' W., on the N - S center of the NW 1/4 of section 1.

Over rolling land.

**19.876**

Point for the NW 1/16 section corner of section 1, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

NW 1/16 S1  
1997

**39.752**

The W 1/16 section corner of sections 1 and 36, north boundary, hereinbefore described.

---

From the center N 1/16 section corner of section 1.

N. 89° 58.2' W., on the E - W center line of the NW 1/4 of section 1.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 1,  
T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

<b>CHAINS</b>	Over rolling land.
<b>20.072</b>	The NW 1/16 section corner of section 1.
<b>40.144</b>	The N 1/16 section corner of sections 1 and 2.
<hr/> <p>Dependent Resurvey of the Subdivision of Section 2, T. 2 N., R. 22 E., Salt Lake Meridian, Utah</p> <hr/>	
<hr/> <p>Reestablishment of the Survey Executed by G.D. Voorhees in 1959</p> <hr/>	
From the 1/4 section corner of sections 2 and 11.	
N. 0° 12.3' W., on the N - S center line of section 2.	
<b>19.854</b>	The center S 1/16 section corner of section 2, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 2, T. 2 N., R. 22 E.
<hr/>	
N. 0° 08.2' E., beginning new measurement.	
<b>9.962</b>	The center N - S 1/64 section corner of section 2, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivisional lines of section 2, T. 2 N., R. 22 E.
From this corner, point selected for B.L.M. Control Station No. 3, bears N 78° 32.3' W., 19.849 chains distance.	
Set a rebar, 12 inches long, 3/4 inches diameter, 2 inches in drill hole, on solid rock.	
<hr/>	
From the E 1/16 section corner of sections 2 and 11.	
N. 0° 04.3' W., on the N - S center line of the SE 1/4 of section 2.	
Over nearly level land.	
<b>19.908</b>	The SE 1/16 section corner of section 2, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 2, T. 2 N., R. 22 E.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 2,  
T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0° 03.6' W., beginning new measurement.

**9.957**

The center N-SE 1/64 section corner of section 2, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 2, T. 2 N., R. 22 E.

From the S 1/16 section corner of sections 1 and 2.

N. 89° 54.5' W., on the E - W center line of the SE 1/4 of section 2.

Over gentle rolling land.

**19.915**

The SE 1/16 section corner of section 2.

N. 89° 54.6' W., beginning new measurement.

**20.002**

The center S 1/16 section corner of section 2.

From the center N-SE 1/64 section corner of section 2.

N. 89° 53.7' W., on the E - W center line of the NW 1/4 of the SE 1/4 of section 2.

Over gentle rolling land.

**19.968**

The center N - S 1/64 section corner of section 2.

From the E - W 1/64 section corner of sections 2 and 11.

N. 0° 07.8' W., on the N - S center line of the SE 1/4, of the SW 1/4 of section 2.

Over nearly level land.

**19.886**

The center E-SW 1/64 section corner of section 2, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 2, T. 2 N., R. 22 E.

From the center S 1/16 section corner of section 2.

N. 89° 47.5' W., on the E - W center line of the SW 1/4 of section 2.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 2,  
T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

9.970

The center E-SW 1/64 section corner of section 2.

Dependent Resurvey of the Subdivision of Section 11,  
T. 2 N., R. 22 E., Salt Lake Meridian, Utah

From the center 1/4 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 0° 03.6' E., on the N - S center line of section 11.

Over nearly level land.

9.921

The center S-N 1/16 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

From the center N-N 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

From this corner, the center S-N 1/64 section corner of section 11, bears S. 0° 02.7' W., 20.084 chains distance.

N. 0° 03.0' E., on the N - S center line of section 11.

Over rolling land.

9.696

The 1/4 section corner of sections 2 and 11.

From the center W-E 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting above a mound of stone, 4 1/2 ft. base to top, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 89° 35.3' W., on the E - W center line section 11.

Over gentle rolling land.

10.035

The center 1/4 section corner of section 11.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 11,  
T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89° 43.7' W., beginning new measurement.

- 9.982** The center E-W 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 89° 33.8' W., beginning new measurement.

- 9.984** The center W 1/16 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

From the NE 1/16 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 0° 03.4' E., on the N - S center line of the NE 1/4 of section 11.

- 9.592** The witness center N-NE 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 0° 03.4' E., beginning new measurement.

- 0.330** True point for the center N-NE 1/64 section corner of section 11, falls in ditch.

- 10.252** The E 1/16 section corner of sections 2 and 11.

From the N 1/16 section corner of sections 11 and 12.

S. 89° 48.8' W., on the E - W center line of the NE 1/4 of section 11.

Over rolling land.

- 19.944** The NE 1/16 section corner of section 11.

From the center W-E 1/64 section corner of section 11.

N. 0° 37.2' W., on the N - S center line of the SW 1/4, of the NE 1/4 of section 11.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 11,  
T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over rolling land.

- 9.745** The SW-NE 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 88° 33.7' W., on the E - W center line of the SW 1/4, of the NE 1/4 of section 11.

Over rolling land.

- 9.911** The center S-N 1/64 section corner of section 11.

From true point for the center N-NE 1/64 section corner of section 11.

N. 89° 06.5' W., on the E - W center line of the NW 1/4, of the NE 1/4 of section 11.

Over rolling land.

- 19.959** The center N-N 1/64 section corner of section 11.

From the center N-SW 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 0° 03.2' E., on the N - S center line of the SW 1/4 of section 11.

Over rolling land.

- 10.152** The center W 1/16 section corner of section 11.

From the NE-SW 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 0° 01.2' W., on the N - S center line of the NE 1/4, of the SW 1/4 of section 11.

Over rolling land.

- 10.069** The center E-W 1/64 section corner of section 11.



DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 11,  
T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the NE-SW 1/64 section corner of section 11.

S. 89° 57.2' W., on the E - W center line of the NE 1/4, of the SW 1/4 of section 11.

Over rolling land.

**9.997** The center N-SW 1/64 section corner of section 11.

---

From the center W 1/16 section corner of section 11.

N. 0° 01.3' E., on the N - S center line of the NW 1/4 of section 11.

Over rolling land.

**9.906** Point for the center S-NW 1/64 section corner of section 11, at proportionate distance; this point was not monumented in the 1959 survey of the subdivision of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, on a solid sandstone, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C S NW 1/64  
S11  
1996

**19.812** The NW 1/16 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

---

From the center E-W 1/64 section corner of section 11.

N. 0° 06.3' E., on the N - S center line of the SE 1/4, of the NW 1/4 of section 11.

Over rolling land.

**9.976** The SE-NW 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

---

From the center S-N 1/64 section corner of section 11.

N. 89° 24.8' W., on the E - W center line of the SE 1/4, of the NW 1/4 of section 11.

Over rolling land.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 11,  
T. 2 N., R. 22 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**9.974** The SE-NW 1/64 section corner of section 11.

---

N. 89° 58.2' W., beginning new measurement.

**9.999** The center S-NW 1/64 section corner of section 11.

---

From the NE-NW 1/64 section corner of section 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 11, T. 2 N., R. 22 E.

N. 0° 05.5' W., on the N - S center line of the NE 1/4, of the NW 1/4 of section 11.

**9.917** The E-W 1/64 section corner of sections 2 and 11.

---

From the center N-N 1/64 section corner of section 11.

S. 88° 45.3' W., on the E - W center line of the NE 1/4, of the NW 1/4 of section 11.

**9.975** The NE-NW 1/64 section corner of section 11.

---

Dependent Resurvey of the Subdivision of Section 12,  
T. 2 N., R. 22 E., Salt Lake Meridian, Utah

---

From the center S-N 1/64 section corner of section 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1959 survey of the subdivision of section 12, T. 2 N., R. 22 E.

N. 0° 08.7' W., on the N - S center line of section 12.

Over rolling land.

**29.890** The 1/4 section corner of sections 1 and 12.

---

From the center S-N 1/64 section corner of section 12.

N. 89° 58.8' W., on the E - W center line of the S 1/2 of the NW 1/4 of section 12.

Over rolling land.

**40.207** The S-N 1/64 section corner of sections 11 and 12.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
M. Ross Workman	Supervisory Cadastral Surveyor

## CERTIFICATE OF SURVEY

We, *Jerry L. Thomas and Richard L. Houston, Cadastral Surveyors*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *3rd day of July, 1996*, we have *dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines, and subdivided sections 1, 2, 11, and 12, and surveyed the subdivision of section 1, in Township 2 North, Range 22 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 27, 1999

Date

*Jerry L. Thomas*  
(Cadastral Surveyor)

April 27, 1999

Date

*Richard L. Houston*  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, the subdivision of sections 1, 2, 11, and 12, and the survey of the subdivision of section 1, in Township 2 North, Range 22 East, Salt Lake Meridian, Utah,*

executed by *Jerry L. Thomas and Richard L. Houston, Cadastral Surveyors*

having been critically examined and found correct, are hereby approved.

April 30, 1999

Date

*Daniel W. Webb*

(Chief Cadastral Surveyor for Utah)